

TECHNICAL DATA



DUO-ED H





DUO-ED

Is a Non Residential Ventilation Unit (NRVU)

EQUIPPED

Equipped with medium efficiency counterflow heat exchanger (Eurovent certified) and centrifugal forward blades multi speed fans.

STRUCTURE

The DUO-ED is made of extruded aluminium profiles and double skin zinc magnesium panels, sandwiched on injected polyurethane foam insulation, thickness 25 mm and density 42 Kg/m³. The position of the ducting connections, made with circular spigots, are easily configurable simply by moving the ducting connection panels. 6 sizes are available in horizontal version, ceiling installation or floor installation, all equipped with automatic partial bypass and medium efficiency heat exchanger. In the vertical version the delivery and/or recovery connections can be rotated upwards (on site). Post heating devices (electric or water), post cooling/heating water coil, direct expansion coil and electrical pre heater device are integrated into the unit are available as additional external module. The filtering sections are: classe ePM1 70% (F7) filters for the fresh air flow and ePM10 50% (M5) filters for the extraction air flow.

CONTROLS

The DUO-ED is supplied with control system and easy connection to the power supply. It's also available the versions with simplified CTR-EASY and CTR08-PH control, the version with EVO-PH control and the version with EVOD-PH-IP control ready for integration in home automation systems (Modbus protocol with Ethernet connection or, upon request, with the addition of the RS485 connection). The new version of our control systems allows the user to shift from one control system to another very quickly and easily by replacing the remote panel even after the installation. It is available the version without control. The CTR08-PH control allows the user to select three levels of fan speed or the possibility to stop them. It automatically manages the By-pass and prevents the heat exchanger freezing by programming the fan speed or, if specifically required, the electric pre-heater resistance (optional item to install inside the unit). The control advises the user if filters need to be replaced (the filter clogging is monitored by a pair of differential pressure sensors) or any other fault. The EVO-PH control has a colored backlit touch screen interface, it gives an intuitive operating status of the unit and it allows programming the fan speed.

This control has a weekly time schedule for automatic unit control, it can be controlled by an external switch to activate the booster and it can automatically adjust the air flow when connected to an air quality sensor. It supports post-air treatment accessories and it advises the user if filters need to be replaced (the filter clogging is monitored by a pair of differential pressure sensors) or if there is any other fault showing where it comes from. The EVOD-PH-IP control has the same characteristics of the EVO-PH version with the addition of the Modbus communication protocol and it allows full control of the unit by the Home Automation software system. If the unit is in a Home Automation network, the webserver lets the user interact with it throughout a device connected to an Internet browser. On request it's also available the version without control system and without electrical cabinet (adjustable pressure switches for filter status and bypass actuator are installed).

NOTE: for the recuperators provided in the "plug & play" version with our CTR08-PH or EVO-PH control, the management of by-pass is automatic, with by-pass motor and temperature probes supplied and installed on board the machine

CTR-EASY (X539-U0)

- . OFF, ON speed 1, speed 2, speed 3
- . ON / OFF by-pass
- . 3 temperature inputs
- . Filter alarms (time-counts or dedicated digital input switches)

IMPORTANT

- . The units put on the market from 1 January 2018 must be with pressure switches (ErP-2018)
- . You can NOT handle the anti-freeze strategy of the exchanger
- . You can NOT manage the by-pass automatically: to make it foresee the unit mounted temperature probes and control display CTR08-PH or EVO-PH.
- . For remote recovery of the recuperator, add the display of CTR08-PH control (2 lights: service and filters) or EVO-PH (vision special machine status and eventual alarm details) with 3 temperature probes


ACCESSORIES

DUO-ED can be equipped with other accessories such as:

- . R.H. of probe, CO₂ or CO₂ / VOC
- . protection roof for outside installation
- . switch speed

For a more complete view of the characteristics of the control panels, please read the specific manuals.

DUO-ED H - TOP VIEW Standard configuration = SH
Mirrored configuration = SY





Counterflow heat exchanger made of aluminum manufactured by RECUTECH
RECUTECH participates in the Eurovent Certification Program



PERFORMANCE (UNI EN 13141-7)

The unit must be ducted properly: UTEK authorizes the use only according to its performance diagram shown into this catalogue
The declared performances are with CLEAN filters, and guaranteed ONLY with the original filters UTEK low pressure drop.





NOTE: for the units DUO-ED 1 and 2, the speed 1V It is NOT wired;
the first speed selectable from the control panel corresponds to the performance curve 2V



PERFORMANCE (UNI EN 13141-7)


The unit must be ducted properly: UTEK authorizes the use only according to its performance diagram shown into this catalogue
The declared performances are with CLEAN filters, and guaranteed ONLY with the original filters UTEK low pressure drop.





PERFORMANCE (UNI EN 13141-7)


The unit must be ducted properly: UTEK authorizes the use only according to its performance diagram shown into this catalogue
The declared performances are with CLEAN filters, and guaranteed ONLY with the original filters UTEK low pressure drop.





HEAT RECOVERY PERFORMANCE (sensible efficiency)

Values referred to the following conditions (UNI EN 308:1998): T_{bs} external air 5°C; U.R. external 72%; T_{bs} environment 25°C; U.R. environment 38%



ECODESIGN

MOD.	$\eta_{t,nvr}$ (%)	q_{nom} (m³/s)	$\Delta p_{s,ext}$ (Pa)	P (kW)	SFP _{int} (W/(m³/s))	SFP _{int,lim 2016} (W/(m³/s))	SFP _{int,lim 2018} (W/(m³/s))	FRONTAL VELOCITY (m/s)	$\Delta p_{s,int}$ (Pa)	η_{fan} (%)	LEAKAGE internal * (%)	LEAKAGE external * (%)
DUO-ED 1	78,2	0,12	100	0,25	1204	1520	1240	1,38	239	18,7	6,1	8,0
DUO-ED 2	75,2	0,27	100	0,68	1104	1406	1126	1,77	200	18,0	1,3	3,7
DUO-ED 2+	77,7	0,35	200	0,90	1184	1468	1188	1,40	346	30,9	2,1	3,8
DUO-ED 3	77,9	0,46	200	1,02	1155	1457	1177	1,84	446	40,1	4,1	2,9
DUO-ED 4	76,7	0,61	250	1,43	1087	1400	1120	1,61	456	41,8	8,7	2,3
DUO-ED 5	76,7	0,82	300	2,34	1067	1367	1087	1,62	380	35,8	4,0	1,3

* Percentage of the nominal flow

VALUES ACCORDING UNI EN 1886: 2008

MOD.	CASING STRENGTH	CASING LEAKAGE	FILTER CLASS	THERMAL TRANSMITTANCE	THERMAL BRIDGE
DUO-ED 1	D1 (M)	L3 (M)	F7 (M)	T4 (M)	TB4 (M)
DUO-ED 2	D1 (M)	L3 (M)	F7 (M)	T4 (M)	TB4 (M)
DUO-ED 2+	D1 (M)	L3 (M)	F7 (M)	T4 (M)	TB4 (M)
DUO-ED 3	D1 (M)	L3 (M)	F7 (M)	T4 (M)	TB4 (M)
DUO-ED 4	D1 (M)	L3 (M)	F7 (M)	T4 (M)	TB4 (M)
DUO-ED 5	D1 (M)	L3 (M)	F7 (M)	T4 (M)	TB4 (M)


TEST LEAKAGE (UNI EN 13141-7)

LEAKAGE	TEST CONDITIONS	DUO-ED 1	DUO-ED 2	DUO-ED 2+	DUO-ED 3	DUO-ED 4	DUO-ED 5
OUTDOOR	Positive pressure 400 Pa	A3	A2	A2	A2	A1	A1
OUTDOOR	Negative pressure 400 Pa	A3	A2	A2	A2	A1	A1
INDOOR	Pressure difference 250 Pa	A3	A1	A1	A2	A3	A2



DUO-ED H 1/2/2+/3


DIMENSIONS (mm) WEIGHT (kg)



MODEL	Dimensions (mm)					Weight (kg)
	A	B	C	Ø	D	
DUO-ED H 1	370	1100	1050	200	185	74
DUO-ED H 2	430	1200	1150	250	215	91
DUO-ED H 2+	500	1460	1300	315	283	142
DUO-ED H 3	550	1460	1300	315	283	150

DUO-ED H 4 and 5

DIMENSIONS (mm) WEIGHT (kg)



MODEL	Dimensions (mm)							Weight (kg)
	A	B	C	Ø	D	E	F	
DUO-ED H 4	640	2300	1500	400	327	350	290	273
DUO-ED H 5	640	2300	1980	400	327	350	290	291



NOISE LEVEL

L_w Sound power level taken in accordance to UNI EN ISO 3747 - CLASS 3

NOISE FROM THE CASE (dB)									
		125 Hz	250 Hz	500 Hz	1000 Hz	2000 Hz	4000 Hz	8000 Hz	L _w dB(A)
DUO-ED 1	4V	51,6	51,2	47,1	43,9	38,3	36,5	45,0	50
DUO-ED 2	4V	57,5	61,3	58,4	52,4	43,9	37,4	45,1	59
DUO-ED 2+	3V	64,7	64,4	58,0	49,6	44,7	36,7	41,6	60
DUO-ED 3	3V	67,1	64,9	58,8	51,2	44,4	36,3	38,7	60
DUO-ED 4	3V	70,4	65,6	58,9	54,2	47,6	39,0	40,0	62
DUO-ED 5	3V	77,2	72,9	61,3	55,3	50,4	42,2	40,7	67

NOISE IN THE SUPPLY AIR DUCTS (dB)									
		125 Hz	250 Hz	500 Hz	1000 Hz	2000 Hz	4000 Hz	8000 Hz	L _w dB(A)
DUO-ED 1	4V	52,6	59,3	61,3	54,8	49,8	46,5	49,8	61
	3V	49,1	54,0	55,9	49,5	41,1	36,9	40,8	55
	2V	47,1	50,1	50,5	46,2	35,2	30,6	39,2	51
	1V	44,0	47,1	46,7	40,4	31,5	30,2	39,7	47

NOISE IN THE SUPPLY AIR DUCTS (dB)									
		125 Hz	250 Hz	500 Hz	1000 Hz	2000 Hz	4000 Hz	8000 Hz	L _w dB(A)
DUO-ED 2	4V	64,5	70,6	72,7	64,4	57,0	62,9	65,6	73
	3V	58,9	66,4	68,1	60,9	50,7	57,3	59,5	68
	2V	53,6	60,8	61,5	56,1	43,1	48,8	49,0	62
	1V	47,6	50,1	52,7	44,4	29,4	33,5	37,7	52

NOISE IN THE SUPPLY AIR DUCTS (dB)									
		125 Hz	250 Hz	500 Hz	1000 Hz	2000 Hz	4000 Hz	8000 Hz	L _w dB(A)
DUO-ED 2+	3V	67,0	78,9	79,6	60,9	63,2	61,0	62,1	75
	2V	66,6	77,1	77,2	59,6	60,8	58,0	58,8	73
	1V	67,5	68,8	75,1	56,4	58,6	53,7	54,5	71

NOISE IN THE SUPPLY AIR DUCTS (dB)									
		125 Hz	250 Hz	500 Hz	1000 Hz	2000 Hz	4000 Hz	8000 Hz	L _w dB(A)
DUO-ED 3	3V	69,0	76,7	78,1	66,3	63,6	61,7	62,7	77
	2V	67,0	72,3	75,2	63,0	60,5	58,4	58,4	74
	1V	64,2	63,9	68,9	55,9	52,8	48,7	46,9	67

NOISE IN THE SUPPLY AIR DUCTS (dB)									
		125 Hz	250 Hz	500 Hz	1000 Hz	2000 Hz	4000 Hz	8000 Hz	L _w dB(A)
DUO-ED 4	3V	70,8	78,9	74,9	72,6	65,2	66,3	68,7	78
	2V	69,3	75,2	71,7	69,3	61,4	62,4	63,6	74
	1V	65,5	71,8	67,4	64,1	57,0	56,9	56,7	70

NOISE IN THE SUPPLY AIR DUCTS (dB)									
		125 Hz	250 Hz	500 Hz	1000 Hz	2000 Hz	4000 Hz	8000 Hz	L _w dB(A)
DUO-ED 5	3V	76,8	86,5	80,0	77,4	72,0	70,2	74,0	83
	2V	76,8	85,5	78,3	76,8	70,1	68,6	72,4	82
	1V	75,4	82,2	76,7	73,4	67,2	66,0	69,3	79

ELECTRICAL DATA

MATCHING	FANS				UNIT DUO-ED		
	Power (W)	Supply	Current max.(A)	Insulation class	Supply	Current max.(A)	Insulation class
DUO-ED 1	2 x 150	230V 50 Hz 1F	2 x 0,7	IP20 CLASS F	230V 50 Hz 1F	1,4	IP20
DUO-ED 2	2 x 290	230V 50 Hz 1F	2 x 1,3	IP20 CLASS F	230V 50 Hz 1F	2,7	IP20
DUO-ED 2+	2 x 400	230V 50 Hz 1F	2 x 3,8	IP20 CLASSE F	230V 50 Hz 1F	7,7	IP20
DUO-ED 3	2 x 400	230V 50 Hz 1F	2 x 3,8	IP20 CLASSE F	230V 50 Hz 1F	7,7	IP20
DUO-ED 4	2 x 550	230V 50 Hz 1F	2 x 4,8	IP20 CLASSE F	230V 50 Hz 1F	9,7	IP20
DUO-ED 5	2 x 750	230V 50 Hz 1F	2 x 9,6	IP20 CLASSE F	230V 50 Hz 1F	19,3	IP20




INSTALLATION DUO-ED from size 1 to size 3

CEILING INSTALLATION

Minimum required space for standard maintenance (mm)

F= filters, H=heat exchanger, V=ventilators




UNIT	Dimensions (mm)				
	A	B	C	D	E
DUO-ED H 1	250	1100	1050	380	500
DUO-ED H 2	350	1200	1150	430	500
DUO-ED H 2+	450	1460	1300	500	500
DUO-ED H 3	500	1460	1300	550	500

FLOOR INSTALLATION

Minimum required space for standard maintenance (mm)

F= filters, H=heat exchanger, V=ventilators



UNIT	Dimensions (mm)				
	A	B	C	D	E
DUO-ED H 1	250	1100	1050	380	500
DUO-ED H 2	350	1200	1150	430	500
DUO-ED H 2+	450	1460	1300	500	500
DUO-ED H 3	500	1460	1300	550	500




INSTALLATION DUO-ED 4 and 5

CEILING INSTALLATION

Minimum required space for standard maintenance (mm)


F= filters, H=heat exchanger, V=ventilators




FLOOR INSTALLATION

Minimum required space for standard maintenance (mm)

F= filters, H=heat exchanger, V=ventilators



STANDARD SIPHON (mm)



N.B. : predict 1 additional siphon if there is the cold water coil BA-AF / AC or DX gas (duct)



GAS R410A coil - DUO-ED 1

DIRECT EXPANSION COIL (R410A)						
Air flow (m³/h)	Tin (°C)	R.H in (%)	Power (kW)	Tout (°C)	R.H: out (%)	Air pressure drop (Pa)
396	25	50	1,96	13,6	86	16
Ø connection (mm)	Fin pitch (mm)	N. Rows	Int.Vol. (dm³)	T evap (°C)	T cond (°C)	
22-16	3,0	3	1,0	5	50	

GAS R410A coil - DUO-ED 2

DIRECT EXPANSION COIL (R410A)						
Air flow (m³/h)	Tin (°C)	R.H in (%)	Power (kW)	Tout (°C)	R.H: out (%)	Air pressure drop (Pa)
828	25	50	3,59	15,4	78,7	53
Ø connection (mm)	Fin pitch (mm)	N. Rows	Int.Vol. (dm³)	T evap (°C)	T cond (°C)	
18-12	2,5	3	1,1	5	50	

GAS R410A coil - DUO-ED 3

DIRECT EXPANSION COIL (R410A)						
Air flow (m³/h)	Tin (°C)	R.H in (%)	Power (kW)	Tout (°C)	R.H: out (%)	Air pressure drop (Pa)
1260	25	50	6,18	14,1	83,6	50
Ø connection (mm)	Fin pitch (mm)	N. Rows	Int.Vol. (dm³)	T evap (°C)	T cond (°C)	
18-12	2,5	3	2,3	5	50	

GAS R410A coil - DUO-ED 4

DIRECT EXPANSION COIL (R410A)						
Air flow (m³/h)	Tin (°C)	R.H in (%)	Power (kW)	Tout (°C)	R.H: out (%)	Air pressure drop (Pa)
1980	25	50	8,01	15,9	77,3	32
Ø connection (mm)	Fin pitch (mm)	N. Rows	Int.Vol. (dm³)	T evap (°C)	T cond (°C)	
18-12	2,5	2	2,6	5	50	

GAS R410A coil - DUO-ED 5

DIRECT EXPANSION COIL (R410A)						
Air flow (m³/h)	Tin (°C)	R.H in (%)	Power (kW)	Tout (°C)	R.H: out (%)	Air pressure drop (Pa)
2700	25	50	10,93	16	76,7	36
Ø connection (mm)	Fin pitch (mm)	N. Rows	Vol.Int (dm³)	T evap (°C)	T cond (°C)	
22-12	2,5	2	3,2	5	50	

SILENCERS NOISE DAMPING TABLE L = 900


		DAMPING (Lw dB)							
Unit	Ø	63	125	250	500	1k	2k	4k	8k
DUO-ED H 1	200	1	3	11	20	41	34	19	17
DUO-ED H 2	250	1	3	8	19	37	20	10	10
DUO-ED H 2+/3	315	1	2	6	16	25	17	9	7
DUO-ED H 4/5	400	1	2	4	10	22	9	7	5

A	Manufacturer's name C.L.A. S.r.l.								
B	Manufacturer's model identifier	DUO-ED 1 EVO-PH SH		DUO-ED 2 EVO-PH SH		DUO-ED 2+ EVO-PH SH		DUO-ED 3 EVO-PH SH	
C	Declared typology	UVNR / UVB		UVNR / UVB		UVNR / UVB		UVNR / UVB	
D	Type of drive installed	Multiple speeds		Multiple speeds		Multiple speeds		Multiple speeds	
E	Type of HRS	other		other		other		other	
F	Thermal efficiency of heat recovery (%)	78.2		76.3		78.1		77.9	
G	Nominal NRVU flow rate (m³/s)	0.12		0.22		0.35		0.46	
H	Effective electric power input (kW)	0.25		0.51		0.92		1.02	
I	SFPint (W/(m³/s)	1204		1062		1194		1156	
J	Face velocity at design flow rate (m/s)	1.4		1.5		1.32		1.8	
K	Nominal external pressure (Pa)	100		150		200		200	
L	Internal pressure drop of ventilation components (Pa)	239		225		316		446	
M	Optional: internal pressure drop of non-ventilation components	-		-		-		-	
N	Static efficiency of fans used in accordance with Regulation (EU) No 327/2011 (%)	18.7		22.1		30.0		40.1	
O	Declared maximum external leakage rate of the casing of ventilation units (%)	8.0		4.6		4.1		2.9	
	Declared maximum internal leakage rate of bidirectional ventilation units or carry over (for regenerative heat exchangers only) (%)	6.1		1.5		2.2		4.1	
	Energy performance, preferably energy classification, of the filters (declared information about the calculated annual energy consumption	ePM1 70% (F7) ePM10 50% (M5)		ePM1 70% (F7) ePM10 50% (M5)		ePM1 70% (F7) ePM10 50% (M5)		ePM1 70% (F7) ePM10 50% (M5)	
Q	Position and description of visual filter warning for RVUs intended for use with filters, including text pointing out the importance of regular filter changes for performance and energy efficiency of the unit	Position and description of visual filter warning for RVUs intended for use with filters, including text pointing out the importance of regular filter changes for performance and energy efficiency of the unit							
R	Casing sound power level (LWA) (dB)	50		58		60		60	
S	Internet address for pre-/dis-assembly instructions	www.utek-air.it							

A	Manufacturer's name C.L.A. S.r.l.		
B	Manufacturer's model identifier	DUO-ED 4 EVO-PH SH	DUO-ED 5 EVO-PH SH
C	Declared typology	UVNR / UVB	UVNR / UVB
D	Type of drive installed	Velocità multiple	Velocità multiple
E	Type of HRS	other	other
F	Thermal efficiency of heat recovery (%)	76,7	76,7
G	Nominal NRVU flow rate (m³/s)	0,61	0,82
H	Effective electric power input (kW)	1,43	2,34
I	SFPint (W/(m³/s)	1087	1067
J	Face velocity at design flow rate (m/s)	1,6	1,6
K	Nominal external pressure (Pa)	250	300
L	Internal pressure drop of ventilation components (Pa)	456	380
M	Optional: internal pressure drop of non-ventilation components	-	-
N	Static efficiency of fans used in accordance with Regulation (EU) No 327/2011 (%)	41,8	35,8
O	Declared maximum external leakage rate of the casing of ventilation units (%)	2,3	1,3
	Declared maximum internal leakage rate of bidirectional ventilation units or carry over (for regenerative heat exchangers only) (%)	8,7	4,0
P	Energy performance, preferably energy classification, of the filters (declared information about the calculated annual energy consumption	ePM1 70% (F7) ePM10 50% (M5)	ePM1 70% (F7) ePM10 50% (M5)
Q	Position and description of visual filter warning for RVUs intended for use with filters, including text pointing out the importance of regular filter changes for performance and energy efficiency of the unit	Position and description of visual filter warning for RVUs intended for use with filters, including text pointing out the importance of regular filter changes for performance and energy efficiency of the unit	
R	Casing sound power level (LWA) (dB)	62	67
S	Internet address for pre-/dis-assembly instructions	www.utek-air.it	



















HORIZONTAL CONFIGURATIONS size 1/2/2+/3
VIEW FROM ABOVE






HORIZONTAL CONFIGURATIONS size 1/2/2+/3
MIRRORED VERSIONS VIEW FROM ABOVE






HORIZONTAL CONFIGURATIONS size 4 e 5
VIEW FROM ABOVE





HORIZONTAL CONFIGURATIONS size 4 and 5
MIRRORED VERSIONS VIEW FROM ABOVE



Dear Customer

Thanks for your attention to the product UTEK , designed and manufactured to ensure the real values to the User : Quality, Safety and Savings on working.



Made in Italy

**AZIENDA CON SISTEMA
DI GESTIONE QUALITÀ
CERTIFICATO DA DNV GL**
ISO 9001

**AZIENDA CON
SISTEMA DI GESTIONE
AMBIENTALE CERTIFICATO
DA DNV**
ISO 14001



the Dealer

DUO-ED H_2020_4_EN



VENTILATION UNIT WITH HEAT RECOVERY FOR COMMERCIAL AND INDUSTRIAL BUILDINGS